

360 DEGREE TYPE-D SOLAR POWERED AIRPORT BARRICADE LIGHT



Part Numbers: 360SC (Screw/Threaded Base); 360BX (Box Base); 360ST (Stake/Post Base)
Dual Function Mode: Flashing &/or Steady Burn Modes All-in-One
Flash Rate: +/- 65 Flashes Per Minute
Power/Energy: 0.4 Watt Solar Panel/2.4 Volt NiMH 2,200 mAh Rechargeable Battery Included
Illumination/Brightness: Multiple High-Intensity Super Bright LEDs; 9 Candelas Each
Operational Requirements: Ready to Operate Right Out of the Box; Maintenance Free
Length of Operation: 3 to 5+ Years
Full Solar Charge: Operates 168+ Hours
Charging Requirements: Re-Charges During Day; No Direct Sunlight Required to Charge
On/Off Switch: Light Automatically Turns On at Dusk & Off at Dawn
Lens Cover Material: Polycarbonate
Base Configurations: Standard Screw/Threaded Base; Universal Box Base; Stake/Post Base
Packaging: 360SC/360ST: 10 Lights per Box; 360BX: 5 Lights per Box (Fully Assembled)
Colors Available: Red; Amber/Yellow; Clear/White

Light Meets or Exceeds FAA Performance Specs; Advisory Circular No. 150/5370-2G Compliant

TYPE-A/C DUAL FUNCTION SOLAR POWERED BARRICADE LIGHT



Part Number: DFO02
Dual Function Mode: Flashing &/or Steady Burn Modes All-in-One
Flash Rate: +/- 65 Flashes Per Minute
Power/Energy: 0.4 Watt Solar Panel/2.4 Volt NiMH Rechargeable 1,600 mAh Battery Included
Illumination/Brightness: 2 High-Intensity Super Bright LEDs; 9 Candelas Each
Operational Requirements: Ready to Operate Right Out of the Box; Maintenance Free
Length of Operation: 3 to 5+ Years
Full Solar Charge: Operates 336+ Hours (Flash Mode); 168+ Hours (Steady Mode)
Charging Requirements: Re-Charges During Day; No Direct Sunlight Required to Charge
On/Off Switch: Light Automatically Turns On at Dusk & Off at Dawn
Lens Cover Material: 7" Polycarbonate Lens with Retro-Reflector Ring
Mounting System: 180 Degree Swivel Box Style Base; Universal Mounting Bracket & Tool
Packaging: 5 Lights per Box (Fully Assembled); All Parts Included
Colors Available: Amber/Yellow; Red; Blue

Light Meets or Exceeds MUTCD Requirements and ITE Specs; NCHRP-350 Certified

TYPE-B SOLAR POWERED HIGH-INTENSITY BARRICADE LIGHT



Part Number: SBL006
Flash Rate: +/- 65 Flashes Per Minute
Power/Energy: 1.5 Watt Solar Panel/3.6 Volt NiMH 4,600 mAh Rechargeable Battery Included
Illumination/Brightness: 9 High-Intensity Super Bright LEDs; 35+ Candelas
Operational Requirements: Ready to Operate Right Out of the Box; Maintenance Free
Length of Operation: 3+ Years
Full Solar Charge: Operates 168+ Hours Flashing; Overcharge Protection Built-In
Charging Requirements: Re-Charges During Day; No Direct Sunlight Required to Charge
On/Off Switch: Operates 24/7 Flashing
Lens Cover Material: Polycarbonate
Mounting System: Box Style Base with Multiple Mounting Options Available
Packaging: 5 Lights per Box (Fully Assembled); All Parts Included
Colors Available: Amber/Yellow; Red

Light Meets or Exceeds MUTCD Requirements and ITE Specs; NCHRP-350 Certified